



Simco
We've Got You Covered

*211 Gunther Ln.
Belle Chasse, LA 70037
Tel: 504.393.9455*

SIMPRIME-135 **HIGH PERFORMANCE MARINE PRIMER**

Description: One component, general-purpose maintenance corrosion inhibitive primer, suitable for use on superstructures and on steel surfaces not normally exposed to water immersion. Excellent paint touch up primer / undercoater. Use over alkyds to upgrade system.

Recommended Uses: Recommended to be used on just about any paintable surface as an undercoater. Also can be used for priming structural steel, bridge, metal roofs and storage tanks in moderate chemicals environments.

Technical Data

Generic Type:	Modified alkyd with rust inhibitive Pigments.
Color:	Yellow, Green, and Red
Flash Point:	80° F
Shelf Life:	One year (subject to re-inspection)
Solids by Weight:	62.0%
Solids by Volume:	43.0%
Weight per Gallon:	12.5 ± 0.2
Recommended DFT:	2.0 - 3.0 mils
Theoretical Coverage:	Approx. 700 sq.ft. / gal. @ 1 mil. DFT.
Dry Temp. Resistance:	200°F
Drying Time @ 75° F:	
To handle:	1 hour
To Topcoat:	8 hours
Recommended Thinner:	Simco T-1 thinner for enamel

Surface Preparation:

All surfaces must be clean, dry, and free from all loose rust, scale, paint or oil. For best results abrasive blast SSPC-SP6 commercial.

Application Data:

Brush, roller, spray.

Safety Precautions:

- (A) Use normal precautions such as gloves, facemasks.
- (B) Adequate ventilation must be maintained.
- (C) Explosion proof lights & electrical equipment.
- (D) Non-Sparking shoes & tools for workers in area.
- (E) This product contains flammable materials. Forbid all flames, smoking and welding in work area.
- (F) Avoid breathing of vapor, contact with skin or eyes. If product comes in contact with skin or eyes, wash thoroughly with water and obtain medical attention.

Non-Warranty:

The technical data listed herein has been compiled for your convenience and guidance, and is based upon our experience and knowledge. However, since we have no control over the use of this information of this product, no warranty expressed or implied, is intended or given. Simco Coatings, Inc. assumes no responsibility whatsoever for coverage, performance, or any other damages, including injuries resulting from use of this information or of products recommended herein.