



Simco
We've Got You Covered

*211 Gunther Ln.
Belle Chasse, LA 70037
Tel: 504.393.9455*

ZINC GUARD-1508 ZINC RICH COATING

Description: Zinc Guard - 1508 is a single package, organic Zinc rich air-dry finish, with high percentage of Zinc pigment. The coating offers a superior corrosion resistance.

Principle Features:

As a corrosion inhibitive air-dry finish for steel and other metals where it is not practical to bake the metal part.
For re-galvanizing welds in galvanized steels.

Technical Data

Drying Time:

To touch: 30 minutes
To handle/hard dry: 4 Hrs. Max

Recommended Thinner:

Xylene or VM & P Naphtha

Generic Type:

Modified epoxy ester

Color and Finish:

Dull gray finish

Flash Point:

103° F

Theoretical Coverage @ 1.0 mil DFT:

700 sq. ft. approx.

Percent Zinc by Weight in Dry Film:

94.0 minimum

Safety Precautions:

- (A) Use normal precautions such as gloves, facemasks.
- (B) Adequate ventilation must be maintained.
- (C) Explosion proof lights & electrical equipment.
- (D) Non-Sparking shoes & tools for workers in area.
- (E) This product contains flammable materials. Forbid all flames, smoking and welding in work area.
- (F) Avoid breathing of vapor, contact with skin or eyes. If product comes in contact with skin or eyes, wash thoroughly with water and obtain medical attention.

Non-Warranty:

The technical data listed herein has been compiled for your convenience and guidance, and is based upon our experience and knowledge. However, since we have no control over the use of this information of this product, no warranty expressed or implied, is intended or given. Simco Coatings, Inc. assumes no responsibility whatsoever for coverage, performance, or any other damages, including injuries resulting from use of this information or of products recommended herein.