



Simco
We've Got You Covered

*211 Gunther Ln.
Belle Chasse, LA 70037
Tel: 504.393.9455*

SHIELD KOTE-2010 W.B. **D-CON STRIPPABLE COATING**

Description: A single package, water based vinyl modified strippable plastic coating.

Principle Features:

- Suitable for decontaminating areas polluted with radioactive materials.
- Seals potential airborne contaminants.
- Shields personnel from smearable contaminants.
- Can be applied over contaminated substrates like steel, concrete, wood and aluminum by spraying or roller.
- Produces an easy strippable film which cleans the substrate with easily disposable compact waste.
- Provides a protective film over clean substrate against future contaminants.

Technical Data

Generic Type:	Vinyl modified plastic resin
Color:	Ocher yellow
Shelf Life:	12 months
Volume Solids:	40-42%
Recommended DFT:	20-30 mils.
Theoretical Coverage @ 25 Mils	26 sq. ft./gal.
Temperature Resistance:	125° F
Drying Time @ 75° F & 70-80% R.H.:	
To Touch:	24 hours
To Full Cure:	48-56 hrs.
Shelf Life:	12 months

Application & Safety Precautions:

- (1) Can be applied by standard airless spray equipment or a roller.
- (2) Use water or butyle cellosolve for cleaning equipment.
- (3) Consult Simco Material Safety Data Sheet for handling of the product.
- (4) Protect materials from freezing.

Non-Warranty:

The technical data listed herein has been compiled for your convenience and guidance, and is based upon our experience and knowledge. However, since we have no control over the use of this information of this product, no warranty expressed or implied, is intended or given. Simco Coatings, Inc. assumes no responsibility whatsoever for coverage, performance, or any other damages, including injuries resulting from use of this information or of products recommended herein.