



Simco
We've Got You Covered

*211 Gunther Ln.
Belle Chasse, LA 70037
Tel: 504.393.9455*

SIMLITE-465
HIGH PERFORMANCE LCF UNDERCOAT/PRIMER

Description: Simlite-465 is a flat alkyd-based undercoat for use as a primer. It provides superior protection for steel exposed to an industrial and marine environment.

Recommended Uses: For painting new work, repaint, trim, plywood, steel and wood siding.

Technical Data

Generic Type:	Alkyd
Color and Finish:	White, black; flat
Flash Point:	104° F
Percent Volume Solids:	50 ± 1%
Solids by Weight:	75.0%
Resin Solids by Weight:	11.0%
Weight per Gallon:	12.0 ± 0.1
Spreading Rate:	750 sq. ft
Drying Time @ 77° F:	
To touch:	2-4 hrs.
To recoat:	16 hrs.

Surface Preparation:

All surfaces to be coated must be dry and free from all dust, dirt, grease, wax, loose paint and rust. Previously painted high gloss surfaces should be dulled by sanding lightly to insure maximum adhesion.

Application Data:

Brush, roller, spray.

Safety Precautions:

- (A) Use normal precautions such as gloves, facemasks.
- (B) Adequate ventilation must be maintained.
- (C) Explosion proof lights & electrical equipment.
- (D) Non-Sparking shoes & tools for workers in area.
- (E) This product contains flammable materials. Forbid all flames, smoking and welding in work area.
- (F) Avoid breathing of vapor, contact with skin or eyes. If product comes in contact with skin or eyes, wash thoroughly with water and obtain medical attention.

Non-Warranty:

The technical data listed herein has been compiled for your convenience and guidance, and is based upon our experience and knowledge. However, since we have no control over the use of this information of this product, no warranty expressed or implied, is intended or given. Simco Coatings, Inc. assumes no responsibility whatsoever for coverage, performance, or any other damages, including injuries resulting from use of this information or of products recommended herein.