



211 Gunther Ln.
Belle Chasse, LA 70037
Tel: 504.393.9455

SILKYD-7210 HIGH PERFORMANCE SILICONE MODIFIED ALKYD PAINT

Description: A high grade, air-dry, VOC compliant, copolymerised silicone alkyd enamel. The ultimate non-chalking finish coat. Tough, resilient coating designed for exceptional exterior durability with superior gloss and color retention. It is an ideal maintenance topcoat with good flexibility and intercoat adhesion.

Suggested Uses:

- Use on primed, smooth metal, glass reinforced plastic (GRP) wood and plastic/composite surface.
- Marine surfaces above the water line, superstructure & overhead cranes.
- Final coat, for new construction or maintenance refresher finish.
- Metal railing, fences, trim, siding and other architectural components.
- Requiring a lasting, aesthetic and protective finish.

Technical Data

Type:	Silicone modified alkyd
Color & Finish:	Various Alkyd Topcoats, Gloss.
Flash Point:	100°F
Solids by Weight:	66 ± 1%
Solids by Volume:	52 ± 1%
VOC:	Average 3.15 Lbs./Gal. or 378 Grm./Ltr. depending on the color
Drying Time Hours @ 75°F:	
To touch:	2 hours
Dry hard:	8 hours
To overcoat:	24 hours
Recommended DFT	2.0 mils / coat
Theoretical Coverage @ 2 mils DFT	Approx. 400 sq. ft/gal.
Shelf Life	12 months
Temperature Resistance	350°F
Recommended Thinner	Mineral Spirits
Shipping Weight	
1's	10.5 lbs.
5's	53 lbs

Surface Preparation:

This product is designed to be applied over blasted or primed steel. Ensure that the surface is free from contaminants.

Method of Application:

Can be applied by conventional spray, brush or a roller. Mix the product thoroughly before use. Thin up to 5% with mineral spirits if required for work ability.

Safety Precautions:

- (A) Use normal precautions such as gloves, facemasks.
- (B) Adequate ventilation must be maintained.
- (C) Explosion proof lights & electrical equipment.
- (D) Non-Sparking shoes & tools for workers in area.
- (E) This product contains flammable materials. Forbid all flames, smoking and welding in work area.
- (F) Avoid breathing of vapor, contact with skin or eyes. If product comes in contact with skin or eyes, wash thoroughly with water and obtain medical attention.

Non-Warranty:

The technical data listed herein has been compiled for your convenience and guidance, and is based upon our experience and knowledge. However, since we have no control over the use of this information of this product, no warranty expressed or implied, is intended or given. Simco Coatings, Inc. assumes no responsibility whatsoever for coverage, performance, or any other damages, including injuries resulting from use of this information or of products recommended herein.

Copyright © 2001-2004 Simco Coatings Inc. All rights reserved.