



**Simco**  
*We've Got You Covered*

*211 Gunther Ln.  
Belle Chasse, LA 70037  
Tel: 504.393.9455*

## SILVER\*LUST-822 HOLD ALUMINUM PAINT

**Description:** An aluminum paint that produces a bright uniform appearance when used in large areas such as elevated water tanks and similar structures. Gives an excellent single coat coverage and has very good long term weathering properties and resistance to moisture and industrial fumes.

### Technical Data

<b>Generic Type:</b>	Alkyd based coating
<b>Color:</b>	Bright, silver
<b>Pigment Type:</b>	Leafing Aluminum Paste conforms to Spec. TT-P-320 Type 2 Class "A"
<b>Flash Point:</b>	101° F
<b>Solids by Volume:</b>	44 ± 1%
<b>Recommended DFT:</b>	1.0 mil. / coat
<b>Theoretical Coverage:</b>	Approx. 700 sq. ft. gal @ 1.0 mil
<b>Viscosity @ 77° F:</b>	65-70 K.U.
<b>Drying Time @ 77° F:</b>	
To Touch:	4 hours
To Recoat:	24 hours
<b>Recommended Thinner:</b>	T-1 Thinner
<b>Dry Heat Resistance:</b>	400° F

### Application:

This paint is of brushing consistency; for spraying, thin paint with mineral spirits if required. Remove all dirt, grease and oil from the surface before painting. If more than one coat is applied allow at least 16 hours air dry between coats. Newly creosoted wood shall be aged at least 6 months prior to the application of paint. When applying by brush, brush one direction only to insure proper leafing of the aluminum.

### Safety Precautions:

- (A) Use normal precautions such as gloves, facemasks.
- (B) Adequate ventilation must be maintained.
- (C) Explosion proof lights & electrical equipment.
- (D) Non-Sparking shoes & tools for workers in area.
- (E) This product contains flammable materials. Forbid all flames, smoking and welding in work area.
- (F) Avoid breathing of vapor, contact with skin or eyes. If product comes in contact with skin or eyes, wash thoroughly with water and obtain medical attention.

### Non-Warranty:

The technical data listed herein has been compiled for your convenience and guidance, and is based upon our experience and knowledge. However, since we have no control over the use of this information of this product, no warranty expressed or implied, is intended or given. Simco Coatings, Inc. assumes no responsibility whatsoever for coverage, performance, or any other damages, including injuries resulting from use of this information or of products recommended herein.